

[This listing of claims will replace all prior versions, and listings, of claims in the application.]

**Listing of Claims:**

1. (Currently amended) Holder for transporting plant cuttings having no support in the ground or soil, comprising at least one carrier and a series of clamping elements which are fixed to the carrier and which are each adapted to clamp a plant cutting, wherein the clamping elements are fixed to the carrier such that plant cuttings clamped in the clamping elements extend substantially parallel to each other, and the center of each of the clamping elements is situated substantially in the same central plane, wherein the central plane extends at a right angle to the plant cuttings, wherein the holder transports whole plant cuttings placed in the holder.
2. (Canceled)
3. (Previously presented) Holder as claimed in claim 1, characterized in that the carrier extends as a strip and that the clamping elements are fixed to the carrier at regular mutual distances.
4. (Previously presented) Holder as claimed in claim 1, characterized in that the clamping elements are each fixed on the same side of the carrier.
5. (Previously presented) Holder as claimed in claim 1, characterized in that the mutual distance between the clamping elements on one side of the carrier is greater than or equal to the mutual distance between the center of the clamping elements so that two carriers with their clamping elements can be placed between each other.
6. (Previously presented) Holder as claimed in claim 1, characterized in that the carrier is substantially flexible.
7. (Previously presented) Holder as claimed in claim 1, characterized in that the carrier is divided into substantially rigid pieces which are coupled in mutually flexible manner.

8. (Previously presented) Holder as claimed in claim 1, characterized in that the carrier has been made substantially from rigid material.
9. (Original) Holder as claimed in claim 8, characterized in that the clamping elements have been made from softer material than the carrier.
10. (Original) Holder as claimed in claim 9, characterized in that the clamping elements have been made in the carrier by injection moulding and that they are connected with the carrier.
11. (Previously presented) Holder as claimed in claim 1, characterized in that the clamping elements each comprise at least two parts, at least one of which is connected resiliently to the carrier.
12. (Original) Holder as claimed in claim 11, characterized in that the parts each take substantially the form of a semi-cylindrical surface, wherein both parts are connected to the carrier such that in the non-loaded situation both parts are separated on either side by a narrow gap.
13. (Previously presented) Holder as claimed in claim 11, characterized in that the inner walls of both parts of the clamping elements have an upward diverging form on one side.
14. (Previously presented) Holder as claimed in claim 11, characterized in that the inner wall of both parts of the clamping elements together have a substantially oval section.
15. (Previously presented) Holder as claimed in claim 12, characterized in that each of the parts is connected to the carrier by at least two bridges.

16. (Original) Holder as claimed in claim 15, characterized in that each of the parts is connected to the carrier by a single bridge element, and that each bridge element extends over a substantial part of the length of the parts of the clamping element.

17. (Original) Holder as claimed in claim 16, characterized in that both parts of the clamping element are mutually connected by a thin strip of material.

18. (Previously presented) Holder as claimed in claim 15, characterized in that the carrier comprises elements which extend parallel to the axis of the clamping elements and which are connected by means of a narrowed portion to parts of the carrier extending substantially in lengthwise direction of the carrier.

19. (Original) Holder as claimed in claim 18, characterized in that the carrier comprises two rods extending in lengthwise direction to which the elements are fixed.

20. (Original) Holder as claimed in claim 19, characterized in that the clamping elements extend partially between the rods.

21. (Original) Holder as claimed in claim 11, characterized in that each of the parts of the clamping elements are connected to the carrier for tilting on an axis extending substantially at a right angle to the plane of the carrier.

22. (Original) Holder as claimed in claim 21, characterized in that each of the parts of the clamping elements are connected to the carrier by means of a connection subject to torsion.

23. (Original) Holder as claimed in claim 22, characterized in that the parts of the clamping elements each comprise a plate which comprises a clamping surface on one side of the connection to the carrier and are provided on the other side with engaging surfaces for moving apart the clamping surfaces in the manner of a lever.

24. (Previously presented) Holder as claimed in claim 9, characterized in that the holder is manufactured by injection moulding or thermoforming of plastic.
25. (Previously presented) Holder as claimed in claim 1, characterized in that the carrier is manufactured from flat material in which at least three lips are punched at the position of each clamping element, which lips are adapted to fixedly clamp the plant cuttings.
26. (Original) Holder as claimed in claim 25, characterized in that the holder is manufactured from paper or from plastic foil.